

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Previously presented) A multiple-protocol home location register comprising:

a receiver for receiving, from a requesting network of at least two requesting networks, a network request according to one of at least two network protocols;

a processor, within the multiple-protocol home location register, for processing the network request utilizing a common source of data and common control procedures for the at least two network protocols to obtain information requested by the network request;

a transmitter, operably coupled to the processor, for relaying the requested information to the requesting network;

wherein the processor comprises one or more protocol gateways, operably coupled to a database that provides the common source of data, wherein the one or more protocol gateways are arranged and constructed to interpret network requests and generate, utilizing the common control procedures for the at least two network protocols, one or more queries to the database.

2. (canceled)

3. (original) The multiple-protocol home location register of claim 1, wherein the processor comprises one or more application gateways, operably coupled to a database that provides the common source of data, wherein the one or more application gateways are arranged and constructed to interpret messages and generate, utilizing the common control procedures, one or more queries to the database.

4

LUC-305 / LaPorta 50-8-56-4

4. (Previously presented) A method comprising the steps of:

receiving, by a multiple-protocol home location register, a network request from a requesting network of at least two requesting networks, wherein the network request is composed according to one of at least two network protocols;

processing the network requests using a common source of data and common control procedures for the two or more protocols to obtain information requested by the network request;

relaying the requested information to the requesting network;

wherein the step of processing comprises the steps of:

interpreting the network request according to rules associated with one of the at least two network protocols;

generating a common command related to the network request;

generating at least one query related to the network request through employment of the common command and relaying the at least one query to a subscriber database;

receiving the requested information from the subscriber database.

5-6. (canceled)

7. (original) The method of claim 4, wherein the step of processing further comprises the step of providing an interworking function between the two or more protocols.

8. (Previously presented) A method comprising the steps of:

receiving, by a first protocol gateway, a first message from a first network utilizing a first network protocol of a plurality of network protocols;

interpreting the first message according to rules associated with the first network protocol;

generating a command based on the interpretation of the first message, wherein the command is one of a set of commands utilized by a database manager, the first protocol gateway, and a second protocol gateway;

generating at least one query based on the command and relaying the at least one query to a subscriber database;

receiving at least one response to the at least one query related to the first message;

relaying the at least one response to the first network.

9. (Previously presented) The method of claim 8, further comprising the steps of:

receiving, by the first protocol gateway, a second message from a second network utilizing a second network protocol of the plurality of network protocols;

interpreting the second message according to rules associated with the second network protocol;

generating a second command based on the interpretation of the first message;

generating at least another query related to the second command and relaying the at least another query related to the message to the subscriber database;

receiving at least one response to the at least another query related to the second message;

relaying, to the second network, the at least one response to the at least another query related to the second message.

10. (original) The method of claim 9, wherein the steps of interpreting and generating are common to the first protocol gateway and the second protocol gateway.

11. (original) The method of claim 8, wherein the step of receiving the message terminates the network protocol.

12. (original) The method of claim 8, wherein the rules associated with the network protocol comprise at least one communication standard.

13. (original) The method of claim 8, wherein the plurality of network protocols comprises at least two of ANSI-41, GSM MAP, SIP, H.323, AAA, and M-IP.

14. (original) The method of claim 8, wherein the network protocols transport at least one of voice, data, and multimedia via at least one of wireline and wireless communication media.

15. (original) The method of claim 8, wherein the database comprises data for a plurality of communication devices and data utilized by at least two networks.

16. (original) The method of claim 15, wherein the data comprises user profile information.

17. (Previously presented) The method of claim 8, further comprising the steps of generating at least another query related to a message from an application server and upon receiving a response to the at least another query, relaying the response to the application server.

18. (original) The method of claim 8, further comprising the step of providing an interworking function between the first network protocol and a second network protocol.

19. (canceled)

20 – 33 (canceled)

34. (Previously presented) A method comprising the steps of:

- receiving a message from a first network via a first protocol gateway;
- processing the message according to a procedure common to the first protocol gateway, a second protocol gateway, and a database;
- generating at least one database query based on the processed message;
- relaying the at least one database query to the database comprising data common to a first network associated with the first protocol gateway and a second network associated with the second protocol gateway;
- receiving a response to the at least one database query and generating a request to the second protocol gateway;
- receiving a reply to the request to the second protocol gateway;
- generating a message based on the reply;
- relaying the message to the first protocol gateway.

8

LUC-305 / LaPorta 50-8-56-4

35. (canceled)

36. (Previously presented) The method of claim 34, wherein the response identifies the second protocol gateway.

37. (Previously presented) The method of claim 34, wherein the response identifies a location for a communication device.

38. (canceled)

39. (Previously presented) The method of claim 34, wherein the reply includes routing information.

40. (original) The method of claim 39, further comprising the step of utilizing the routing information to route a call to a communication device located in a coverage area of the second network.